



Installation Quick Start Guide for AQT-W1 Important Installation Instructions

- 1 Locate filter below the refrigerator. Slowly turn the cartridge 1/4 turn counter-clockwise and remove. Remove knob from old filter.
- 2 Remove all packaging, and remove the red protective cap from the top. Note installation date on reminder sticker and place in a convenient visible location.
- 3 Slide knob from old filter onto new filter. Insert filter into refrigerator and turn 1/4 turn clockwise until firmly seated.
- 4 Run water for 3 minutes through the dispenser to flush the filter.
- 5 Reset the "replace filter" light. Refer to your refrigerator owner's manual for reset procedure.
- 6 Attach the included water filter replacement calendar label according to the label instructions.



Tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.

For further questions or assistance please call (866) 218-8473.
Monday - Friday 8am to 5pm Pacific Standard Time

WARNING

A newly-installed water filter cartridge may cause water to spurt from the dispenser until all the air is removed. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing.

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. This filter must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Failure to follow instructions and operation specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. The filter bypass plug MUST be used when a filter replacement cartridge is not installed.

The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.