



AQT-LK12

ICE & WATER FILTER SYSTEM



ADVANCED MULTI-STAGE FILTRATION TECHNOLOGY

This AQT-LK12 Ice & Water Filter System contains a compressed carbon block which provides tremendous capacity to reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on its surface and within the structure which can absorb impurities like a sponge. It adsorbs and holds other types of impurities on its surface like a magnet. This filter also breaks down other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with fresh and clean tasting water and ice.

List price: \$81.99

FILTER FEATURES:

- Reduces Chlorine taste and odor, sand, rust, silt, sediment and impurities that may be present in your drinking water.
- Provides your family with great tasting, premium quality drinking water for pennies per gallon.
- Enjoy better-tasting ice cubes, coffee, juices, vegetables, etc.
- Provides 1-Micron filtration.
- Leaves in minerals and fluoride that may be present in your drinking water.
- Includes a permanently mounted head which can be installed vertically or horizontally.
- Built-in bypass valve in the head allows for filter change without shutting off water supply to system.
- Includes 1/4" fittings that fit both copper and plastic tubing.
- Easy DIY quarter turn replacement filter.
- Includes flush valve to activate system, saving significant installation time and money.
- Can be easily installed anywhere along the water line that feeds the refrigerator, including under your kitchen sink or in the basement.
- Designed to provide up to 6 months of life or 300 gallons.
- AquaThrift® filters are easy to replace and provide clean, clear, great tasting water for you, your family and your pets.



Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

This filter has been tested by the manufacturer against ANSI/NSF Standard 42 for the reduction of chlorine taste and odor.

SPECIFICATIONS:

Approximate Dimensions:	13" H x 3" W x 3.5" D (33 cm H x 7.6 cm W x 8.9 cm D)
Flow Rate:	0.5 GPM (1.89 lpm)
Operating Temperature:	40°-100° F (4.4°-38° C)
Operating Water Pressure Range:	30-100 psi (207 kPa-690 kPa)
Life:	6 months or 300 gallons
Micron Rating:	1-Micron